



August 2018

SIMPLE INGENUITY

LEVEL.IT ADJUSTABLE PEDESTALS

- Simple, extended height range pedestal
- Patented design features exclusive internal coupler
- Durable commercial quality
- Fast and easy installation promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Long lasting solution with no maintenance over time
- Made in the U.S.A.



US Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

SPECIFICATIONS

- Supports 750 lbf (3.34 kN) FS:3 per pedestal
- Select 1/8 or 3/16 inch (3.175 or 4.5 mm) tab size for pedestals
- Level.it adjustable system height range is 2 to 12 inches (51 to 304.8 mm)
- Accessories available for heights from 1/8 to 2 inches (3.175 to 51 mm)
- Pedestals made of high density copolymer polypropylene
- Contains 20% post-industrial recycled material
- Impervious to water, mold, and freeze/thaw cycles
- Made in the U.S.A.

		Model No.	Description	Range	Notes
Pedestals		LC-18 LC-316	Adjustable Pedestal	2" - 4 3/4" (51 - 121 mm)	
		C1	Gray Coupler	Adds up to 1 1/2" (38.1 mm) each	
		C4	Black Coupler	Adds up to 4" (101.6 mm) each	
Accessories	-	LT18 LT316	Spacer Tab	1/8" (3.175 mm) wide 3/16" (4.5 mm) wide	Select 1/8" (3.175 mm) or 3/16" (4.5 mm) Tab Size
		VT18 VT316	Ultra Low Height Pedestal	1/8" (3.175 mm)	
	444	HD25-18 HD25-316 HD50-18 HD50-316 HD75-18 HD75-316	Fixed Height Stackable Pedestals	1/4" (6.35 mm) 1/2" (12.7 mm) 3/4" (19.05 mm)	Stack up to 4 Supports 1250 lbf (5.56 kN) FS:3 per Pedestal
		LO-18 LO-316	Low Height Adjustable Pedestal	1 1/4" - 2" (31.75 - 51 mm)	
		B11	Rubber Flexible Shim	1/16" (1.588 mm)	
		PS1	Plastic Rigid Shim	1/8" (3.175 mm)	
		LD4	Base Leveler	Adds 1/4" (6.35 mm) to Pedestal height Stack up to 4 total to base of Pedestals	Maximum of 1" per foot slope (8%)
	6-	FS-1	Fastening Kit*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals	
		FS-12	12" Spline*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals when additional protection against wind uplift is required	
		JT	Joist Top	Adds 3/16" (4.5 mm) in height	Works with 2x and 4x lumber on Adjustable Pedestals
		FIB	Floating Insulation Base	12" x 12" x 11/16" (304.8 x 304.8 x 17.463 mm) For use over roofing systems with 20-40 psi (137.895 - 275.79 kPa) bearing capacity	
		FFB	Floating Foundation Base	12" x 12" x 1/4" (304.8 x 304.8 x 6.35 mm) For use under Pedestals on grade (soil)	

*US #8,302,356 Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

