



VERSADJUST
Adjustable Pedestals

STRENGTH AND SUPERIOR FUNCTIONALITY

January 2018

VERSADJUST ADJUSTABLE PEDESTALS

- Integral base leveling to correct for sloped substrates
- Each center-loaded pedestal supports 1250 pounds
- Quick-clip extenders to reach heights fast - up to 36 inches
- Pedestal bracing system for additional stability and heights over 24 inches
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Unique patented design
- Made in the U.S.A.



US Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

SPECIFICATIONS

- Supports 1250 lbf (5.56 kN) FS:3 per pedestal
- Select 1/8 or 3/16 inch (3.175 or 4.5 mm) tab size for pedestals
- Integrated base levelers accommodate 0 to 1/2 inch per foot slope (0-4%)
- Adjustable system height range is 2 1/4 to 36 inches (57.15 to 914.4 mm)
- Bison Brace System required for 24 to 36 inches (609.6 to 914.4 mm)
- Accessories available for heights from 1/8 to 2 1/4 inches (3.175 to 57.15 mm)
- Contains 20% post-industrial recycled material
- Impervious to water, mold, and freeze/thaw cycles
- Made in the U.S.A.

	Model No.	Description	Range	Notes
Pedestals	 V1-18 V1-316	Adjustable Pedestal	2 1/4" - 2 3/4" (57.15 - 69.85 mm)	--
	 V2-18 V2-316	Adjustable Pedestal	2 3/4" - 3 3/4" (69.85 - 95.25 mm)	--
	 V3-18 V3-316	Adjustable Pedestal	3 3/4" - 5 3/4" (95.25 - 146.05 mm)	--
	 V4-18 V4-316	Adjustable Pedestal	5 3/4" - 9" (146.05 - 228.6 mm)	--
		Quick Clip Extender	Adds up to 4" (101.6 mm) each	Insert VC2 into V4 base or another VC2 to reach up to 36" (914.4 mm)
Tabs	 VT18 VT316	Spacer Tab	1/8" (3.175 mm) wide 3/16" (4.5 mm) wide	Select 1/8" (3.175 mm) or 3/16" (4.5 mm) Tab Size
	 VT18 VT316	Ultra Low Height Pedestal	1/8" (3.175 mm)	--
		Fixed Height Stackable Pedestals	1/4" (6.35 mm) 1/2" (12.7 mm) 3/4" (19.05 mm)	Stack up to 4
	 LO-18 LO-316	Low Height Adjustable Pedestal	1 1/4" - 2" (31.75 - 51 mm)	Supports 750 lbf (3.34 kN) FS:3 per Pedestal
Accessories		Rubber Flexible Shim	1/16" (1.588 mm)	--
		Plastic Rigid Shim	1/8" (3.175 mm)	--
		Base Leveler	Adds 1/4" (6.35 mm) to Pedestal height Stack up to 4 total to base of Pedestals	Maximum of 1" per foot slope (8%)
		Wood Tile Fastening Kit*	Secures Bison Wood Tiles to Bison Adjustable Pedestals	
		Joist Top	Adds 3/16" (4.5 mm) in height	Works with 2x and 4x lumber on Adjustable Pedestals
		Floating Insulation Base	12" x 12" x 11/16" (304.8 x 304.8 x 17.463 mm)	For use over roofing systems with 20-40 psi (137.895 - 275.79 kPa) bearing capacity
		Floating Foundation Base	12" x 12" x 1/4" (304.8 x 304.8 x 6.35 mm)	For use under Pedestals on grade (soil)

*US #8,302,356 Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

