



VERSADJUST
Adjustable Pedestals

STRENGTH AND SUPERIOR FUNCTIONALITY

August 2018

VERSADJUST ADJUSTABLE PEDESTALS

- Integral base leveling to correct for sloped substrates
- Each center-loaded pedestal supports 1250 pounds
- Quick-clip extenders to reach heights fast - up to 36 inches
- Pedestal bracing system for additional stability and heights over 24 inches
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Unique patented design
- Made in the U.S.A.



US Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

SPECIFICATIONS

- Supports 1250 lbf (5.56 kN) FS:3 per pedestal
- Select 1/8 or 3/16 inch (3.175 or 4.5 mm) tab size for pedestals
- Integrated base levelers accommodate 0 to 1/2 inch per foot slope (0-4%)
- Adjustable system height range is 2 1/4 to 36 inches (57.15 to 914.4 mm)
- Bison Brace System required for 24 to 36 inches (609.6 to 914.4 mm)
- Accessories available for heights from 1/8 to 2 1/4 inches (3.175 to 57.15 mm)
- Contains 20% post-industrial recycled material
- Impervious to water, mold, and freeze/thaw cycles
- Made in the U.S.A.

	Model No.	Description	Range	Notes
Pedestals	 V1-18 V1-316	Adjustable Pedestal	2 1/4" - 2 3/4" (57.15 - 69.85 mm)	--
	 V2-18 V2-316	Adjustable Pedestal	2 3/4" - 3 3/4" (69.85 - 95.25 mm)	--
	 V3-18 V3-316	Adjustable Pedestal	3 3/4" - 5 3/4" (95.25 - 146.05 mm)	--
	 V4-18 V4-316	Adjustable Pedestal	5 3/4" - 9" (146.05 - 228.6 mm)	--
	 VC2	Quick Clip Extender	Adds up to 4" (101.6 mm) each	Insert VC2 into V4 base or another VC2 to reach up to 36" (914.4 mm)
Tabs	 VT18 VT316	Spacer Tab	1/8" (3.175 mm) wide 3/16" (4.5 mm) wide	Select 1/8" (3.175 mm) or 3/16" (4.5 mm) Tab Size
	 VT18 VT316	Ultra Low Height Pedestal	1/8" (3.175 mm)	--
	 HD25-18 HD25-316 HD50-18 HD50-316 HD75-18 HD75-316	Fixed Height Stackable Pedestals	1/4" (6.35 mm) 1/2" (12.7 mm) 3/4" (19.05 mm)	Stack up to 4
	 LO-18 LO-316	Low Height Adjustable Pedestal	1 1/4" - 2" (31.75 - 51 mm)	Supports 750 lbf (3.34 kN) FS:3 per Pedestal
	 B11	Rubber Flexible Shim	1/16" (1.588 mm)	--
	 PS1	Plastic Rigid Shim	1/8" (3.175 mm)	--
Accessories	 LD4	Base Leveler	Adds 1/4" (6.35 mm) to Pedestal height Stack up to 4 total to base of Pedestals	Maximum of 1" per foot slope (8%)
	 FS-1	Fastening Kit*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals	
	 FS-12	12" Spline*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals when additional protection against wind uplift is required	
	 JT	Joist Top	Adds 3/16" (4.5 mm) in height	Works with 2x and 4x lumber on Adjustable Pedestals
	 FIB	Floating Insulation Base	12" x 12" x 11/16" (304.8 x 304.8 x 17.463 mm)	For use over roofing systems with 20-40 psi (137.895 - 275.79 kPa) bearing capacity
	 FFB	Floating Foundation Base	12" x 12" x 1/4" (304.8 x 304.8 x 6.35 mm)	For use under Pedestals on grade (soil)

*US #8,302,356 Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

