



SCREWJACK
Adjustable Pedestals

DEPENDABILITY AND RELIABILITY

SCREWJACK ADJUSTABLE PEDESTALS

August 2018

- Bison's patented original ScrewJack pedestal
- Trusted brand and proven performance since 1994
- Pedestal bracing system for additional stability and heights over 24 inches
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Unique patented design
- Sold exclusively through Oldcastle Westile
- Made in the U.S.A.



US Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

BISON INNOVATIVE PRODUCTS | 701 OSAGE STREET, BLDG 2, UNIT 120, DENVER, CO 80204 USA | 800-333-4234 | WWW.BISONIP.COM

SPECIFICATIONS

- Supports 1000 lbf (4.45 kN) FS:3 per pedestal
- Pedestal tab width 3/16 inch (4.5 mm)
- Adjustable system height range is 1 1/4 to 36 inches (32 to 914.4 mm)
- Bison Brace System required for 24 to 36 inches (609.6 to 914.4 mm)
- Accessories available for heights from 1/8 to 1 1/4 inches (3.175 to 57.15 mm)
- Pedestals made of High Density Copolymer Polypropylene
- Contains 20% post-industrial recycled material
- Impervious to water, mold, and freeze/thaw cycles
- Made in the U.S.A.

	Model No.	Description	Range	Notes
Pedestals	 B1	Adjustable Pedestal	1 1/4" - 2" (32 - 51 mm)	--
	 B2	Adjustable Pedestal	2" - 3" (51 - 76 mm)	--
	 B3	Adjustable Pedestal	3" - 4 3/4" (76 - 121 mm)	--
	 B4	Adjustable Pedestal	4 3/4" - 7 3/4" (121 - 197 mm)	--
	 C4	Black Coupler	Adds up to 4" (101.6 mm) each	Screw C4 into B3 or B4 base or another C4 to reach up to 36" (914.4mm)
Accessories	 VT316	Ultra Low Height Pedestal	1/8" (3.175 mm)	--
		Fixed Height Stackable Pedestals	1/4" (6.35 mm) 1/2" (12.7 mm) 3/4" (19.05 mm)	Stack up to 4
	 B11	Rubber Flexible Shim	1/16" (1.588 mm)	--
	 PS1	Plastic Rigid Shim	1/8" (3.175 mm)	--
	 LD4	Base Leveler	Adds 1/4" (6.35 mm) to Pedestal height Stack up to 4 total to base of Pedestals	Maximum of 1" per foot slope (8%)
	 FS-1	Fastening Kit*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals	
	 FS-12	12" Spline*	Secures Bison Wood Tiles or Paver Trays to Bison Pedestals when additional protection against wind uplift is required	
	 FIB	Floating Insulation Base	12" x 12" x 11/16" (304.8 x 304.8 x 17.463 mm) For use over roofing systems with 20-40 psi (137.895 - 275.79 kPa) bearing capacity	
	 FFB	Floating Foundation Base	12" x 12" x 1/4" (304.8 x 304.8 x 6.35 mm) For use under Pedestals on grade (soil)	

US #8,302,356 Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

