Get CEU Credits, Details, & Specifications online at www.bisonip.com Innovative Products 701 Osage Street, Unit 120, Denver, CO 80204 USA Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988 EMail info@bisonip.com Web www.bisonip.com FLOATING INSULATION PAVER BASES CAN BE USED TO SPREAD THE WEIGHT OF THE DECK OVER A LARGER PEDESTAL SURFACE AREA (12" x 12") FLOATING INSULATION BASES (DO NOT ATTACH TO SUBSTRATE) **REQUIRED OVER ROOFING** SYSTEMS WITH LESS THAN 40 PSI BEARING CAPACITY (20 PSI MINIMUM) PEDESTALS ON FLOATING INSULATION BASES (FIBs) 4.125" (TYP) IMPORTANT: THE PEDESTAL MUST BE PLACED IN THE CENTER OF THE FLOATING INSULATION BASE FOR PROPER INSTALLATION. Π THE FIB MAY BE TRIMMED TO ACCOMMODATE NARROW PERIMETER PLACEMENT IF NECESSARY. TRIM AT LEAST 4.125" AWAY FROM THE CENTER RIBS AS SHOWN BY THE SCORE LINES IN THE DIAGRAM TO THE RIGHT. 4.125" (TYP) THE FIB IS NOT RECOMMENDED FOR USE WITH VT AND HD25 FIXED HEIGHT PEDESTALS. PEDESTAL PLACEMENT AND TRIMMING GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS 1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS. 2. DRAWINGS NOT TO SCALE. 3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com FLOATING INSULATION BASE

FIB INSTALLATION