


701 Osage Street, Unit 120, Denver, CO 80204 USA Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988 EMail info@bisonip.com Web www.bisonip.com

BISON VERSADJUST PEDESTALS MUST BE BRACED FOR STABILITY TO ACCOMMODATE HEIGHTS IN EXCESS OF 24" UP TO A MAXIMUM OF 36". STRUCTURAL PERIMETER CONTAINMENT, WITH NO MORE THAN 1/8" WIDTH SPACING, ON ALL SIDES OF THE PEDESTAL DECK SYSTEM IS REQUIRED. IN ADDITION, ONE OR TWO LEVELS OF BISON BRACES MAY BE USED ON ANY VERSADJUST INSTALLATION WHERE ADDITIONAL STABILITY IS DEEMED NECESSARY.

IMPORTANT: REFER TO VERSADJUST PRODUCT SPECIFICATIONS TO ENSURE PROPER USE AND INSTALLATION. FIND VERSADJUST SPECIFICATIONS AT www.BISONIP.com.



GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

- 1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.
- 2. DRAWINGS NOT TO SCALE.
- 3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com



EXTREME CAVITY HEIGHT BRACING

24" TO 36" BRACING REQUIREMENTS