
Get CEU Credits, Details, & Specifications online at www.bisonip.com




701 Osage Street, Unit 120, Denver, CO 80204 USA Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988 EMail info@bisonip.com Web www.bisonip.com






B11

1/16" (1.6 mm) FLEXIBLE SHIM 5-7/8" (149 mm) DIAMETER USED FOR SLOPE COMPENSATION, SOUND DAMPENING, AND/OR FINAL LEVELING. STACK NO MORE THAN 2 SHIMS.






1/8" (3.2 mm) RIGID SHIM 5-7/8" (149 mm) DIAMETER USED FOR SLOPE COMPENSATION AND/OR FINAL LEVELING, STACK NO MORE THAN 2 SHIMS.




VT18 / VT316 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS 4-11/16" (119 mm) DIAMETER USED FOR LOW CAVITY HEIGHTS AND/OR SURFACE MATERIAL SPACING.




HD25-18 / HD25-316

1/4" (6 mm) FIXED HEIGHT STACKABLE PEDESTAL 5-7/8" (149 mm) DIAMETER 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS USED FOR LOW CAVITY HEIGHTS. STACK UP TO 4 FIXED HEIGHT PEDESTALS TOGETHER.



HD50-18 / HD50-316 1/2" (13 mm) FIXED HEIGHT STACKABLE PEDESTAL 5-7/8" (149 mm) DIAMETER USED FOR LOW CAVITY HEIGHTS. STACK UP TO 4 FIXED HEIGHT PEDESTALS TOGETHER.



HD75-18 / HD75-316 3/4" (19 mm) FIXED HEIGHT STACKABLE PEDESTAL 5-7/8" (149 mm) DIAMETER 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS 1/8" (3.2 mm) OR 3/16" (4.5 mm) TABS USED FOR LOW CAVITY HEIGHTS. STACK UP TO 4 FIXED HEIGHT PEDESTALS TOGETHER.

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.

2. DRAWINGS NOT TO SCALE.

3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com

SHIMS AND FIXED HEIGHT PEDESTALS

STACKABLE PEDESTALS FROM 1/4" TO 3"