

SCREWJACK Adjustable Pedestals

DEPENDABILITY AND RELIABILITY

July 2023

SCREWJACK ADJUSTABLE PEDESTALS





- Bison's patented original ScrewJack pedestal
- Trusted brand and proven performance since 1994
- Pedestal bracing system for additional stability and heights over 24 inches
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Unique patented design
- Sold exclusively through Oldcastle Westile
- Made in the U.S.A.




©2013-2023 United Construction Products, Inc. All Rights Reserved.
Covered by one or more patents or pending patents.

SPECIFICATIONS

- Supports 1000 lbs (454 kg) FoS:3 per pedestal
- Pedestal tab width 3/16 inch (4.5 mm)
- Adjustable system height range is 1 ¼ to 36 inches (32 to 914 mm)
- Bison Brace System required for 24 to 36 inches (610 to 914 mm)
- Accessories available for heights from 1/8 to 1 ¼ inches (3.2 to 57 mm)
- Pedestals made of high density copolymer polypropylene
- Contains 20% post-industrial recycled material

	Model No.	Description	Range	Notes
Pedestals	 B1	Adjustable Pedestal	1-1/4" to 2" (32 to 51 mm)	--
	 B2	Adjustable Pedestal	2" to 3" (51 to 76 mm)	--
	 B3	Adjustable Pedestal	3" to 4-3/4" (76 to 121 mm)	--
	 B4	Adjustable Pedestal	4-3/4" to 7-3/4" (121 to 197 mm)	--
Accessories	 C4	Coupler	Adds up to 4" (102 mm)	Screw C4 into B3 or B4 base or another C4 to reach up to 36" (914 mm)
	 VT316	Ultra Low Height Pedestal	1/8" (3.2 mm)	--
	 HD25-316 HD50-316 HD75-316	Fixed Height Stackable Pedestals	1/4" (6 mm) 1/2" (13 mm) 3/4" (19 mm)	Stack up to 4 Supports 1250 lbs (567 kg) FoS:3 per Pedestal
	 B11	Flexible Shim	1/16" (1.5 mm)	--
	 PS1	Rigid Shim	1/8" (3.2 mm)	--
	 LD4	Base Leveler	Adds 1/4" (6 mm)	Stack up to 4 total to base of Pedestals for 1/4" per foot (2%) slope compensation each
	 FS-1	Wood Tile Fastening Kit	Fastens Wood Tiles to Adjustable Pedestals with long screw, and HD50 or HD75 Fixed Height Pedestals with short screw	
	 FS-12 FS-12-WT	12" Fastening Spline 3/16" (4.5 mm) Tab	Fastens Wood Tiles or Paver Trays to Adjustable Pedestals with long screw, and HD50 or HD75 Fixed Height Pedestals with short screw	
	 JS	Joist Saddle Attachment	Adds 1/2" (13 mm)	Works with 2 x and 4 x lumber alone or on any Bison Pedestal
	 FIB	Floating Insulation Base	12" x 12" x 11/16" (305 x 305 x 17 mm) For use over roofing systems with 20 to 40 psi insulation	
	 FFB	Floating Foundation Base	12" x 12" x 1/4" (305 x 305 x 6 mm) For use over soil	

IMPORTANT: Refer to ScrewJack product specifications to ensure proper use and installation. For more information visit www.bisonip.com.



FIXED HEIGHT PEDESTALS

HD50 (1/2") HD75 (3/4")

ADJUSTABLE PEDESTALS

B1 (1-1/4" to 2") B2 (2" to 3") B3 (3" to 4-3/4") B4 (4-3/4" to 7-3/4") B3 + C4 (7-3/4" to 9") B4 + C4 (9" to 12")

NOTE: Pedestals each shown with one optional LD4 slope compensation accessory.