



LEVEL.IT  
Adjustable Pedestals

## SIMPLE INGENUITY

September 2018

### LEVEL.IT ADJUSTABLE PEDESTALS






- Simple, extended height range pedestal
- Patented design - features exclusive internal coupler
- Durable commercial quality
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Long lasting solution with no maintenance over time
- Made in the U.S.A.



US Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

# SPECIFICATIONS

- Supports 750 lbf (3.34 kN) FS:3 per pedestal
- Select 1/8 or 3/16 inch (3.175 or 4.5 mm) tab size for pedestals
- Level.it adjustable system height range is 2 to 12 inches (51 to 304.8 mm)
- Accessories available for heights from 1/8 to 2 inches (3.175 to 51 mm)
- Pedestals made of high density copolymer polypropylene
- Contains 20% post-industrial recycled material
- Impervious to water, mold, and freeze/thaw cycles
- Made in the U.S.A.

|             | Model No.  | Description                         | Range  | Notes   |
|-------------|--|-------------------------------------|--|---|
| Pedestals   |  LC-18<br>LC-316  | Adjustable Pedestal                 | 2" - 4 3/4"<br>(51 - 121 mm)   | --  |
|             |  C1   | Gray Coupler                        | Adds up to 1 1/2"<br>(38.1 mm) each  | --  |
|             |  C4   | Black Coupler                       | Adds up to 4"<br>(101.6 mm) each   | --  |
| Tabs        |  LT18<br>LT316  | Spacer Tab                          | 1/8" (3.175 mm) wide<br>3/16" (4.5 mm) wide  | Select 1/8" (3.175 mm) or<br>3/16" (4.5 mm) Tab Size              |
|             |  VT18<br>VT316  | Ultra Low Height Pedestal           | 1/8" (3.175 mm)  | --  |
| Accessories |  HD25-18 HD25-316<br>HD50-18 HD50-316<br>HD75-18 HD75-316 | Fixed Height<br>Stackable Pedestals | 1/4" (6.35 mm)<br>1/2" (12.7 mm)<br>3/4" (19.05 mm)  | Stack up to 4<br>Supports 1250 lbf (5.56 kN)<br>FS:3 per Pedestal |
|             |  LO-18<br>LO-316   | Low Height<br>Adjustable Pedestal   | 1 1/4" - 2"<br>(31.75 - 51 mm)   | --  |
|             |  B11  | Rubber Flexible Shim                | 1/16" (1.588 mm)   | --  |
|             |  PS1  | Plastic Rigid Shim                  | 1/8" (3.175 mm)  | --  |
|             |  LD4  | Base Leveler                        | Adds 1/4" (6.35 mm) to<br>Pedestal height<br>Stack up to 4 total to<br>base of Pedestals   | Maximum of 1" per<br>foot slope (8%)                              |
|             |  FS-1   | Fastening Kit*                      | Secures Bison Wood Tiles or Paver Trays to Bison Pedestals   |   |
|             |  FS-12  | 12" Spline*<br>3/16" (4.5 mm) Tab   | Secures Bison Wood Tiles or Paver Trays to Bison Pedestals<br>when additional protection against wind uplift is required                 |   |
|             |  JT   | Joist Top                           | Adds 3/16" (4.5 mm)<br>in height   | Works with 2x and 4x lumber on<br>Adjustable Pedestals            |
|             |  FIB  | Floating Insulation Base            | 12" x 12" x 11/16" (304.8 x 304.8 x 17.463 mm)<br>For use over roofing systems with 20-40 psi<br>(137.895 - 275.79 kPa) bearing capacity |   |
|             |  FFB  | Floating Foundation Base            | 12" x 12" x 1/4" (304.8 x 304.8 x 6.35 mm)<br>For use under Pedestals on grade (soil)  |   |

\*US #8,302,356 Patent and Patents Pending. Copyright 2018 United Construction Products, Inc. All Rights Reserved.

