

SAFETY DATA SHEET: Bison Paver Tray

Bison Innovative Products	Toll Free 800-333-4234	Hours Mon-Fri 8am -5pm MST
701 Osage Street, Bldg 2, Unit 120	Phone 303-892-0400	info@bisonip.com
Denver, CO 80204	Fax 303-825-5988	www.bisonip.com

Section 1 Product Information

Product Name	Bison 2cmTray/ Bison 2cmPAVERTray/ PT-2424
Component Synonyms	Tray: Galvanized (Hot Dipped) Sheet—Carbon Steel; Galvannealed (Hot Dipped) Sheet—Carbon Steel; UPI.GalXC Sheet—Carbon Steel Adhesive Square: Butyl Rubber
Chemical Family	Natural Inorganic Products

Section 2 – Hazard(s) Identification

<p>Hazard Identification</p>	<p>As sold, this product is not considered hazardous under Cal-OSHA 8CCR Section 5194 and OSHA 29 CFR Parts 1910.1200 Hazard Communication Standard, steel products are considered articles/ mixtures due to further processing which may produce dusts and/or fumes. However, individual customer processes, (such as welding, sawing, brazing, melting, grinding, abrasive blasting, and machining) may result in the formation of fumes, dust (combustible or otherwise), and/ or particulates which may present the following hazards:</p> <p>OSHA Hazards: Carcinogen Skin Sensitizer Target Organ Effect</p> <p>Target Organs: Respiratory system</p> <p>GHS Classification: Carcinogenicity (Category 2) Skin Sensitization (Category 1) Specific Target Organ Toxicity (STOT)-Repeated Exposure (Category 1) Specific Target Organ Toxicity (STOT)-Single Exposure (Category 3) Toxic to Reproduction (Category 2) Acute Toxicity-Oral (Category 4) Eye Irritation (Category 2B)</p> <div style="text-align: center;">  </div> <p>SIGNAL WORD: WARNING</p> <p>Hazard Statement(s): May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to lungs through prolonged or repeated inhalation exposure. Harmful if swallowed. May cause respiratory irritation. Causes eye irritation.</p> <p>Precautionary Statement(s): Do not handle until all safety precautions have been read and understood. Do not breathe dusts/ fumes/ spray. Wear protective gloves/ protective clothing/ eye protection/ face protection. Contaminated work clothing must not be allowed out of the workplace.</p>
-------------------------------------	---

SAFETY DATA SHEET: Bison Paver Tray

	<p>Use only outdoors or in well ventilated areas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed, concerned or feel unwell: Get medical advice/ attention. If in eyes: Rinse cautiously with water/ eye wash solution for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Hazard(s) Not Otherwise Classified (HNOC): None known. Unknown Acute Toxicity Statement (mixture): None known. These products do not contain asbestos. Under normal condition these products do not release hazardous materials after installation and are not considered hazardous. Waste and residues should be disposed of in accordance with local authority requirements.</p>
--	---

Section 3 – Composition/ Information on Ingredients

Product Component	Ingredient Name	CAS Number	Percentage by wt.
Tray-Base Metal	Iron	7439-89-6	>90.0
Tray-Alloying Elements	Calcium	7440-70-2	0.10 max.
	Carbon	7440-44-0	0.60 max.
	Copper	7440-50-8	0.50 max.
	Manganese	7439-96-5	0.90 max.
	Phosphorus	8049-19-2	0.15 max.
	Silicon	7440-21-3	0.60 max.
	Sulfur	7704-34-9	0.04 max.
Tray-Metallic Coating	Aluminum	7429-90-5	0.055 max.
	Antimony	7440-36-0	0.011 max.
	Iron	7439-89-6	0.8 max.
	Lead	7439-92-1	0.004 max.
	Zinc	7440-66-6	0.15-9.1

Notes: Galvanized sheet surfaces may be chemically treated, with trace amounts of chromate solution (apprx. 1-2 mg/ft² per side or 0.002% of total product weight) to prevent humid storage stain, and/ or phosphate solution (<300 mg/ft² or <0.3%) to enhance paint adherence and formability. Surface may also be treated with small amounts (<0.05%) of corrosion-inhibiting oil. All commercial steel products may contain small various elements in addition to those specified. These small quantities (less than 0.1%) may exist as intentional additions, or as "trace" or "residual" elements that generally originate in the raw materials used. These elements may include: aluminum, antimony, arsenic, boron, cadmium, calcium, chromium, cobalt, columbium, copper, lead, molybdenum, nickel, silicon, tin, titanium, vanadium, and zirconium.

Product Component	Ingredient Name	CAS Number	Percentage by wt.
Adhesive Square	Limestone	1317-65-3	50-60%
	Butene, homopolymer	9003-27-4	20-30%
	Hydrous magnesium silicate	14807-96-6	10-20%
	Precipitated calcium carbonate	471-34-1	1-10%

SAFETY DATA SHEET: Bison Paver Tray

Section 4 – First-Aid Measures

Inhalation	This product as sold/ shipped is not a likely form of exposure as all constituents are encapsulated. However, during further processing (cutting, grinding, burning, etc.), potential exposure may occur. If inhaled and breathing becomes difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Eye Contact	This product as sold/ shipped is not a likely form of exposure. However, during further processing (cutting, grinding, burning, etc.), potential exposure may occur. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation develops and persists.
Skin Contact	If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of adhesive. Wash contact areas with soap and water. If irritation or rash occurs: seek medical advice/ attention. Wash contaminated clothing before reuse.
Ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/ effects, acute and delayed	This product as sold/ shipped is not a likely form of exposure as all constituents are encapsulated. However, during further processing (cutting, grinding, burning, etc.), potential exposure may occur. Breathing or swallowing dusts/ fumes may cause irritation to the nose, throat, and digestive tract. <u>Repeated exposure to dusts/ particulates could expose individuals to constituents including Lead which is known to the state of California to cause Male and Female developmental issues.</u>
Indication of immediate medical attention and special treatment needed	Treat symptomatically. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Section 5 – Fire-Fighting Measures

Suitable extinguishing media	Foam. Dry Chemical Powder. Carbon Dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use jet as an extinguisher, as this will spread the fire.
Special hazards arising from the chemical	Tray: Metallic coating will begin to melt around 800°F (427°C) and the metal will begin to melt around 2750°F (1510°C). This product will proceed to a liquid and will form irritating and toxic gaseous metallic oxides at extremely high temperatures. Adhesive Square: During fire, gases hazardous to health may be formed.
Unusual fire or explosion hazards	Not applicable for solid product. DO NOT use water on molten metal or adhesive.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and self-contained breathing apparatus (SCBA). Structural firefighter's protective clothing will only provide limited protection.
Fire-fighting equipment/ instructions	Use standard fire-fighting procedures and consider the hazards of other involved materials. DO NOT breathe fumes.

Section 6 – Accidental Release Measures

Spill/ Leak Procedures	Not applicable for this product as sold/ shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery and/ or disposal in accordance with federal, state, and local regulations.
------------------------	---

SAFETY DATA SHEET: Bison Paver Tray

Regulatory Requirements	Follow applicable OSHA regulations (29 CFR 1910.120 and Cal-OSHA 8CCR 5192) and all other pertinent state and federal requirements.
Disposal	Follow applicable federal, state, and local regulations.

Section 7 – Handling and Storage

Precautions for safe handling	Trays can become very hot when sitting in the sun. Use caution when handling and always wear gloves. Avoid prolonged exposure to dusts/ fumes and control exposure as necessary. Avoid unnecessary handling of the adhesive square as frequent contact could result in accidental contamination leading to further exposure. Cut only in well ventilated areas. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Practice good housekeeping.
Conditions for safe storage	Store away from acids and incompatible materials (section 10 of the SDS).

Section 8 – Exposure Control Measures / Personal Protection

Product Component	Ingredient Name	CAS Number	Cal-OSHA PEL ¹	OSHA PEL ¹	ACGIH TLV ²
Tray-Base Metal	Iron	7439-89-6	5 mg/m ³ -Iron Oxide fume	10 mg/m ³ -Iron Oxide fume	5 mg/m ³ -Iron Oxide dust and fume
Tray-Alloying Elements	Calcium	7440-70-2	2 mg/m ³ -Calcium Oxide	5 mg/m ³ -Calcium Oxide	2 mg/m ³ -Calcium Oxide
	Carbon	7440-44-0	10 mg/m ³ -Total dust (PNOR) ³ 2 mg/m ³ – Respirable fraction (PNOR)	15 mg/m ³ -Total dust (PNOR) ³ 5 mg/m ³ – Respirable fraction (PNOR)	10 mg/m ³ -Inhale fraction ⁴ (PNOS) ⁵ 3 mg/m ³ – Respirable fraction ⁶ (PNOS)
	Copper	7440-50-8	0.1 mg/m ³ -Fume (as Cu) 1 mg/m ³ – Dusts & mists (as Cu)	0.1 mg/m ³ -Fume (as Cu) 1 mg/m ³ – Dusts & mists (as Cu)	0.2 mg/m ³ -Fume 1 mg/m ³ – Dusts & mists (as Cu)
	Manganese	7439-96-5	0.2 mg/m ³ (C)-Fume & Mn compounds	0.5 mg/m ³ (C)-Fume & Mn compounds	0.2 mg/m ³
	Phosphorus	8049-19-2	10 mg/m ³ -Total dust (PNOR) 5 mg/m ³ – Respirable fraction (PNOR)	15 mg/m ³ -Total dust (PNOR) 5 mg/m ³ – Respirable fraction (PNOR)	10 mg/m ³ -Total dust (PNOS) 3 mg/m ³ – Respirable fraction (PNOS)
	Silicon	7440-21-3	10 mg/m ³ -Total dust 5 mg/m ³ – Respirable fraction	10 mg/m ³ -Total dust 5 mg/m ³ – Respirable fraction	10 mg/m ³
	Sulfur	7704-34-9	10 mg/m ³ -Total dust (PNOR) 5 mg/m ³ – Respirable fraction (PNOR)	15 mg/m ³ -Total dust (PNOR) 5 mg/m ³ – Respirable fraction (PNOR)	10 mg/m ³ -Inhalable fraction (PNOS) 3 mg/m ³ – Respirable fraction (PNOS)
Tray-Metallic Coating	Aluminum	7429-90-5	10 mg/m ³ -Aluminum metal & oxide total dust 5 mg/m ³ – Respirable fraction	15 mg/m ³ -Total dust 5 mg/m ³ – Respirable fraction	10 mg/m ³ -Metal dust 5 mg/m ³ – Welding fume
	Antimony	7440-36-0	0.5 mg/m ³	0.5 mg/m ³	0.5 mg/m ³

SAFETY DATA SHEET: Bison Paver Tray

	Iron	7439-89-6	5 mg/m ³ -Iron Oxide fume	10 mg/m ³ -Iron Oxide fume	5 mg/m ³ -Iron Oxide dust and fume
	Lead	7439-92-1	0.05 mg/m ³ ⁷	0.05 mg/m ³ ⁷	0.05 mg/m ³ ⁷
	Zinc	7440-66-6	5 mg/m ³ -Fume 10 mg/m ³ – Total Dust 5 mg/m ³ – Respirable fraction	5 mg/m ³ -Fume 15 mg/m ³ – Total Dust 5 mg/m ³ – Respirable fraction	5 mg/m ³ -Fume 10 mg/m ³ – Fume (STEL) 10 mg/m ³ – Dust

¹OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (“C”) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during the workday.

²Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted.

³PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the PNOR limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction.

⁴Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH TLVs and BEIs Appendix D, paragraph C.

⁵PNOS (Particulates Not Otherwise Specified). Particulates identified under the PNOS heading are “nuisance dusts” containing no asbestos and <1% crystalline silica. A TWA-TLV of 10 mg/m³ for inhalable particulate and 3 mg/m³ for respirable particulate has been recommended.

⁶Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH TLVs and BEIs Appendix D, paragraph C.

⁷The 8-hour PEL is 50 µg/m³. If an employee is exposed to lead for more than 8 hours in any work day, the PEL as a TWA for that day, shall be reduced according to the following formula: Maximum permissible limit (in µg/m³) = 400 divided by hours worked in that day. The Action Level is 30 µg/m³ averaged over an 8-hour period.

Product Component	Ingredient Name	CAS Number	Cal-OSHA PEL ¹	OSHA PEL ¹	ACGIH TLV ²	US NIOSH
Adhesive Square	Limestone	1317-65-3	0.3 mg/m ³ – Total Dust 0.1 mg/m ³ – Respirable fraction	15 mg/m ³ - Total dust 5 mg/m ³ – Respirable fraction	10 mg/m ³ -Total dust 3 mg/m ³ – Respirable fraction	10 mg/m ³ -Total dust 5 mg/m ³ – Respirable fraction
	Butene, homopolymer	9003-27-4	No established limit	No established limit	No established limit	No established limit
	Hydrous magnesium silicate	14807-96-6	No established limit	20 mppcf	2 mg/m ³ – Respirable fraction	No established limit
	Precipitated calcium carbonate	471-34-1	10 mg/m ³ – Total Dust 5 mg/m ³ – Respirable fraction	15 mg/m ³ - Total dust 5 mg/m ³ – Respirable fraction	10 mg/m ³	10 mg/m ³ -Total dust 5 mg/m ³ – Respirable fraction
Biological Limit Values		No biological exposure limits noted for the ingredient(s).				
Engineering Controls		Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.				

SAFETY DATA SHEET: Bison Paver Tray

Administrative Controls	Do not use compressed air to clean-up dust or particles generated by grinding, sawing, or cutting operations.			
Personal Protective Equipment	Eyes	Skin/Hand	Other	Respiratory
	Use of safety glasses with side shields or goggles required for any cutting, grinding, drilling, etc. operation. A face shield may also be required depending on the circumstance.	Wear suitable gloves to prevent contact, cuts and abrasions.	Wear appropriate clothing to prevent any possibility of contact to undesired parts of the body.	Not normally required. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fumes at levels exceeding the exposure limits. Seek professional advice prior to respirator selection and use. Follow Cal-OSHA and Federal OSHA respiratory regulations (8CCR Section 5144; 29 CFR 1910.134) and, if necessary, wear a NIOSH-Approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen.
Thermal Hazards	When material is heated, wear gloves to protect against thermal burns. Be aware that the adhesive will soften to a liquid form as it heats up.			
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

Section 9 – Physical and Chemical Properties

Tray:

Physical State: Solid	Flammability Classification: Non-flammable, non-combustible	Surface Tension: N/A
Appearance and Odor: Metallic Gray, Odorless	LEL: N/A	Vapor Pressure: N/A
Odor Threshold: N/A	UEL: N/A	Vapor Density (Air=1): N/A
Formula Weight: N/A	Auto-Ignition Temperature: N/A	pH: N/A
Density: 7.85 g/cc	Water Solubility: Insoluble	% Volatile: N/A
Specific Gravity (H₂O=1, at 4°C): 7.85	Other Solubilities: N/A	Evaporation Rate: N/A
Flash Point: N/A	Boiling Point: N/A	Freezing/ Melting Point: Base Metal - 2750°F Metallic Coating – 800-900°F
Flash Point Method: N/A	Viscosity: N/A	
Burning Rate: N/A	Refractive Index: N/A	

Adhesive:

Physical State: Semi-Solid	Flammability Classification: Not Classified as a flammable hazard	Surface Tension: N/A
Appearance and Odor: Black, tacky solid. Faint, mild odor	LEL: N/A	Vapor Pressure: N/A

SAFETY DATA SHEET: Bison Paver Tray

Odor Threshold: N/A	UEL: N/A	Vapor Density (Air=1): N/A
Formula Weight: N/A	Auto-Ignition Temperature: N/A	pH: N/A
Density: N/A	Water Solubility: N/A	% Volatile: N/A
Specific Gravity (H ₂ O=1, at 4°C): 1.61 g/cm ³	Other Solubilities: N/A	Evaporation Rate: N/A
Flash Point: N/A	Boiling Point: N/A	Freezing/ Melting Point: N/A
Flash Point Method: N/A	Viscosity: N/A	Decomposition Temperature: >200°C (392°F)
Burning Rate: N/A	Refractive Index: N/A	

Section 10 – Stability and Reactivity

Stability	The product is stable and non-reactive under normal conditions of use, storage and transport.
Polymerization	Hazardous reactions or polymerization will not occur.
Chemical Incompatibilities	Tray: Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion. Adhesive: Strong oxidizing agents.
Conditions to Avoid	Tray: Storage with strong acids or calcium hypochlorite. Adhesive: None.
Hazardous Decomposition Products	Tray: Thermal oxidative decomposition of galvanized steel products can produce fumes containing oxides of zinc, iron, and manganese as well as other elements. Adhesive: Upon decomposition, this product may yield carbon monoxide, carbon dioxide, isobutane and other combustion products are possible.

Section 11 – Toxicological Information – Information on likely exposure routes

Ingestion	As sold and under normal use this product does not present an ingestion, inhalation, skin, or eye hazard. However, during further processing (cutting, grinding, burning, etc.), potential exposure may occur from dust or fumes. Ingestion of dust generated may cause nausea or vomiting. Inhalation of dusts, fumes, or metal oxides generated during processing especially in high concentrations can produce symptoms of metal fever. Typical symptoms last 12-48 hours and are characterized by metallic taste in the mouth, dryness, and irritation of the throat, followed by weakness, muscle pain, fever, and chills. Dust may irritate the skin , and contact with hot material can cause thermal burns which may result in permanent damage. Repeated or prolonged contact with chemical surface treatments or oil residue may cause skin irritation, dermatitis, ulceration, or allergic reactions in sensitized individuals. Dust or fumes produced during further processing may irritate the eyes , as can direct contact to the eye from a piece of heated metal or the adhesive. Heating steel products with surface treatments, oil coatings, or acrylic films may produce emissions which may irritate the eyes.
Inhalation	
Skin Contact	
Eye Contact	
Symptoms related to the physical, chemical, and toxicological characteristics	Symptoms may include itching, burning, redness, and tearing of the eyes. Mechanical irritation of the skin. Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Directly contacting the adhesive to one's eyes may cause temporary irritation.
Acute Toxicology	Cutting the trays can potentially generate ozone. Ozone can cause irritation of eyes, nose, and respiratory tract.

SAFETY DATA SHEET: Bison Paver Tray

Tray	Iron (CAS 7439-89-6) Acute Oral LD50	Rat	30 g/kg
	Manganese (CAS 7439-96-5) Acute Oral LD50	Rat	9 g/kg
Adhesive	Product (mixture calculation method) Oral: LD ₅₀ >5000 mg/kg Dermal: LD ₅₀ >2600 mg/kg Inhalation: LD ₅₀ >8 mg/kg		
	Limestone (CAS 1317-65-3) Oral: LD ₅₀ >6450 mg/kg Dermal: LD ₅₀ : No Data Inhalation: LD ₅₀ : No Data		
	Butene, homopolymer (CAS 9003-27-4) Oral: LD ₅₀ >5000 mg/kg Dermal: LD ₅₀ >3000 mg/kg Inhalation: LD ₅₀ >17.3 mg/L	Dermal (rabbit) Inhalation (mist)	
	Hydrous magnesium silicate (CAS 14807-96-6) Oral: LD ₅₀ : No Data Dermal: LD ₅₀ : No Data Inhalation: LD ₅₀ : No Data		
	Precipitated calcium carbonate (CAS 471-34-1) Oral: LD ₅₀ >2000 mg/kg Dermal: LD ₅₀ >2000 mg/kg Inhalation: LD ₅₀ >3 mg/L		
Skin corrosion/ irritation	Contact with dusts or particulates produced by cutting, grinding, drilling may be abrasive and mildly irritate the skin. Particulates may cause a red-brown pigmentation of the skin following repeated or prolonged exposure.		
Serious eye damage/ eye irritation	Contact with dusts or particulates produced by cutting, grinding, drilling may be abrasive and irritate the eyes causing stinging, redness, and watering. Direct contact of the adhesive is harmful to the eyes.		
Respiratory Sensitization	Not expected to be a respiratory sensitizer.		
Skin Sensitization	Repeated or prolonged exposure to the adhesive may cause skin disorders.		
Carcinogenicity	<p>Tray: The International Agency for Research on Cancer (IARC), the National Laboratory Toxicology Program (NTP), and OSHA do not list steel products as carcinogens. IARC identifies lead and welding fumes as group 2B carcinogen (possibly carcinogenic to humans). EPA lists lead as Group B2 (probable human carcinogen) based on a combination of sufficient evidence in animals and inadequate evidence in humans. When specified, a hexavalent chromium passivation treatment is applied to the product surface. IARC lists hexavalent chromium compounds as Group 1 (sufficient evidence for carcinogenicity in humans). NTP lists certain hexavalent chromium compounds as Group 1 (known to be carcinogenic). The American Conference of Governmental Industrial Hygienists (ACGIH) lists hexavalent chromium compounds as A1 (confirmed human carcinogen).</p>		

SAFETY DATA SHEET: Bison Paver Tray

Reproductive Toxicity	No information available on the reproductive hazard of this material. However, manganese and lead, are constituents, and have demonstrated some effects on the male and female reproductive system. The expected exposure is not sufficient enough to classify the material as a reproductive hazard.
Specific Target Organ Toxicity-Single Exposure	Not expected to cause organ effects from a single exposure.
Specific Target Organ Toxicity-Repeated Exposure	Limestone (CAS 1317-65-3) may cause damage to organs (lungs) through prolonged or repeated exposure. Repeated exposure to dust/ particulates from cutting and/or grinding the tray may cause damage to male and female reproductive organs.
Aspiration Hazard	Not applicable.
Chronic effects	Tray: Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases. Exposure to manganese fume/ dust can affect the central nervous system (apathy, drowsiness, weakness, and other chronic symptoms such as postural tremors). Adhesive: Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/ chapping and oil acne.
Further Information	<u>In its manufactured and shipped state, this product is considered non-hazardous.</u> Processing may generate hazardous fumes and dusts. Manganese CAS# 7439-96-5 Repeated administration of manganese resulted in limited evidence of male reproductive effects in laboratory animals. The adverse effects included decreased spermatids, spermatocytes and degeneration of seminiferous tubules. Chronic administration of certain inorganic manganese salts has resulted in limited evidence of central nervous system effects in laboratory animals. The effects included degenerative changes in basal ganglionic cells. These effects do not meet the criteria for classifying it as a reproductive toxicant.

Section 12 – Ecological Information

Ecotoxicity (aquatic & terrestrial)	Individual components of the product when tested have been found to be toxic to the environment. Metal dusts may migrate into the soil and groundwater and be ingested by wildlife as follows.		
	Iron (CAS 7439-89-6) Aquatic <i>Fish</i> LC50	Channel catfish (<i>Ictalurus punctatus</i>)	>500mg/l, 96 hours
	Zinc (CAS 7440-66-6) Aquatic <i>Fish</i> LC50	Rainbow trout, Donaldson Trout (<i>Oncorhynchus mykiss</i>)	0.24 mg/l, 96 hours
Environmental Fate	No data available.		
Environmental Degradation	No data available.		
Bioaccumulative potential	No data available.		
Soil Absorption/ Mobility	No data available for the product. However, individual components of the product have been found to be absorbed by plants from soil.		

SAFETY DATA SHEET: Bison Paver Tray

Mobility in general	Not relevant due to the form of the product. No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product. This product does not contain any of the controlled substances listed in the Annexes to the Montreal Protocol at concentrations of \geq 0.1%.
----------------------------	--

Section 13 – Disposal Considerations

Disposal	Collect and dispose at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated materials. Do not dispose material into any storm water or sewage system.
Container cleaning and disposal	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may contain residual products, follow label warnings even after the container is emptied. Dispose of in accordance with applicable federal, state, and local regulations.

Section 14 – Transport Information

The DOT, IATA, and IMDG do NOT regulate this product as a dangerous good.

Section 15 – Regulatory Information

OSHA Regulations	Tray: Under some use conditions, this material may be considered hazardous in accordance with OSHA 29 CFR 1910.1200. Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): The product as a whole is not listed. However individual components of the product are listed. OSHA Specifically Regulated Substance: Lead (29 CFR 1910.1025). This material has not been identified as a carcinogen by NTP, IARC, or OSHA. Adhesive: Contents of this MSDS comply with OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Tray: Not regulated. Adhesive: Not listed or exempt from listing on the TSCA Inventory.
CERCLA Hazardous Substance List (40 CFR 302.4)	Tray: The product as a whole is not listed. However, individual components of the product are listed: Antimony (CAS 7440-36-0) LISTED Copper (CAS 7440-50-8) LISTED Lead (CAS 7439-92-1) LISTED Manganese (CAS 7439-96-5) LISTED Zinc (CAS 7440-66-6) LISTED Adhesive: Not listed.
Superfund Amendments and Reauthorization Act of 1986 (SARA)	Tray/ Adhesive: Immediate Hazard-No Delayed Hazard-No Fire Hazard-No Pressure Hazard-No Reactivity Hazard-No
SARA 302 Extremely hazardous substance	Tray: Not listed. Adhesive: Not listed.
SARA 311/312 Hazardous chemical	Tray: No. Adhesive: Chronic health hazard.

SAFETY DATA SHEET: Bison Paver Tray

<p>SARA 313 (TRI reporting)</p>	<p>Tray: <i>Chemical Name:</i> <i>CAS Number:</i> <i>% by wt.:</i> Antimony 7440-36-0 0.011 max. Copper 7440-50-8 0.50 max. Lead 7439-92-1 0.004 max. Zinc 7440-66-6 0.5-19.0 Manganese 7439-96-5 0.0-1.35 Adhesive: Not regulated.</p>
<p>Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List</p>	<p>Tray: Manganese (CAS 7439-96-5) Adhesive: Not regulated.</p>
<p>Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)</p>	<p>Tray: Not regulated. Adhesive: Not regulated.</p>
<p>Safe Drinking Water Act (SDWA)</p>	<p>Tray: Not regulated. Adhesive: Not regulated.</p>
<p>RCRA (40CFR261)</p>	<p>Tray: Steel scrap is not regulated as a solid waste or a hazardous waste under this act. If product dusts and/ or fumes from processing operations are not recycled, they are considered to be a solid waste and may be classified as a hazardous waste depending on the toxicity characteristics of the dust as defined within 40CFR261.24.</p>
<p>State Regulations</p>	<p>Tray: This product as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations.</p> <ul style="list-style-type: none"> • Massachusetts Right-to-Know – Substance List <ul style="list-style-type: none"> ○ Aluminum (CAS 7429-90-5) ○ Antimony (CAS 7440-36-0) ○ Copper (CAS 7440-50-8) ○ Lead (CAS 7439-92-1) ○ Manganese (CAS 7439-96-5) ○ Zinc (CAS 7440-66-6) • New Jersey Worker and Community Right-to-Know Act <ul style="list-style-type: none"> ○ Aluminum (CAS 7429-90-5) ○ Antimony (CAS 7440-36-0) ○ Copper (CAS 7440-50-8) ○ Lead (CAS 7439-92-1) ○ Manganese (CAS 7439-96-5) ○ Sulfur (CAS 7704-34-9) ○ Zinc (CAS 7440-66-6) • Pennsylvania Worker and Community Right-to-Know Law <ul style="list-style-type: none"> ○ Aluminum (CAS 7429-90-5) ○ Antimony (CAS 7440-36-0) ○ Copper (CAS 7440-50-8) ○ Lead (CAS 7439-92-1) ○ Manganese (CAS 7439-96-5) ○ Zinc (CAS 7440-66-6) ○ Calcium (CAS 7440-70-2) ○ Silicon (CAS 7440-21-3) ○ Sulfur (CAS 7704-34-9) • Rhode Island Right-to-Know <ul style="list-style-type: none"> ○ Aluminum (CAS 7429-90-5) ○ Antimony (CAS 7440-36-0) ○ Copper (CAS 7440-50-8)

SAFETY DATA SHEET: Bison Paver Tray

- Lead (CAS 7439-92-1)
- Manganese (CAS 7439-96-5)
- Zinc (CAS 7440-66-6)
- **California Proposition 65 Carcinogens & Reproductive Toxicity (CRT):**
⚠WARNING: This product can expose you to chemicals including nickel (metallic), which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to – www.P65Warnings.ca.gov.
 Though the product is NOT hazardous in its as shipped condition and only becomes hazardous when exposed to post-processing dusts/particulates from cutting, grinding, etc.
- **Listed Substance**
 - This product may contain an extremely small amount of lead in the metallic coating. An extremely small amount of hexavalent chromium passivation treatment may be applied to the surface of the galvanized steel product. Lead and hexavalent chromium are materials known to the State of California to cause cancer or reproductive toxicity. In addition, the product may also possibly contain trace quantities (generally much less than 0.1%) of other metallic elements known to the State of California to cause cancer or reproductive toxicity. These include arsenic (inorganic), cadmium and nickel.

Adhesive:

- **Massachusetts Right-to-Know – Substance List**
 - Amorphous Silica (Respirable Dust) (CAS 112926-00-8).
- **New Jersey Worker and Community Right-to-Know Act**
 - Not regulated.
- **Pennsylvania Worker and Community Right-to-Know Law**
 - Not regulated.
- **Rhode Island Right-to-Know**
 - Not regulated.
- **California Proposition 65 Carcinogens & Reproductive Toxicity (CRT):**
⚠WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to – www.P65Warnings.ca.gov.
- **California Proposition 65 – CRT: Listed date/ Carcinogenic substance**
 - Lead (CAS 7439-92-1) from cutting/ grinding post-processing—Male and Female Reproductive Toxicity [February 27, 1987].
 - Silica, crystalline (CAS N/A) encapsulated in the adhesive and not expected to become airborne under normal use conditions-- Cancer [October 1, 1988].

International Inventories

Tray:		
Country(s) or region:	Inventory name:	On Inventory (yes/ no)*:
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
Adhesive:		
Country(s) or region:	Inventory name:	On Inventory (yes/ no)*:
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

SAFETY DATA SHEET: Bison Paver Tray

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No
<p>*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).</p>		
Other Regulations:	<p>Tray: WHMIS Classification (Canadian): This product, Galvanized (Hot Dipped) Sheet-Carbon Steel is not listed as a whole. However, individual components are listed: Manganese—Classified B4, D2A. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.</p>	

Section 16 – Other Information

Original Issue Date	06/15/2016
Version Number (Revised)	2.0 (09/25/2018) – Switched butyl adhesive formulation. 3.0 (04/04/2019) – Updated California Proposition 65 Warning.
References	<p>ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices USS-POSCO Galvanized (Hot Dipped) Sheet—Carbon Steel MSDS Version 4/14/2015 DeVan 825.11-SDS, 2018-06-14—DeVan Butyl</p>

Disclaimer: The data in this Material Safety Data Sheet applies only to the specific product designated herein and does not relate to use in combination with any other material or process. The data given here is based on current knowledge and experience. The purpose of this MSDS is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customer and the protection of the environment. The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. United Construction Products, dba Bison Innovative Products and its subsidiaries make no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded. United Construction Products, dba Bison Innovative Products and its subsidiaries will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	25-8775-6	Version Number:	5.00
Issue Date:	09/30/15	Supersedes Date:	05/11/15

SECTION 1: Identification

1.1. Product identifier

3M™ Polyurethane Adhesive Sealant 550 Fast Cure (Various Colors)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
62-5265-3430-0		62-5265-3435-9	
62-5265-3530-7		62-5265-3930-9	
62-5265-5230-2		62-5265-5235-1	
62-5265-5238-5		62-5265-8530-2	
62-5265-9530-1		62-5266-3430-8	
62-5266-3435-7		62-5266-3530-5	
62-5266-3930-7		62-5266-5230-0	
62-5266-5235-9		62-5267-3430-6	
62-5267-3435-5		62-5267-3530-3	
62-5267-3930-5		62-5267-3936-2	
62-5267-5230-8		62-5267-5235-7	
62-5267-5238-1		62-5267-8530-8	

1.2. Recommended use and restrictions on use

Recommended use

Fast curing., Sealant

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1A.

Carcinogenicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms



Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.

Causes damage to organs:
sensory organs |

Causes damage to organs through prolonged or repeated exposure:
nervous system |

May cause damage to organs through prolonged or repeated exposure:
sensory organs |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
In case of inadequate ventilation wear respiratory protection.
Wear protective gloves.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane Polymer	Trade Secret*	25 - 35 Trade Secret *
Poly(Vinyl Chloride) Polymer	9002-86-2	20 - 35 Trade Secret *
Plasticizer Mixture	Trade Secret*	10 - 30 Trade Secret *
Xylene	1330-20-7	< 6 Trade Secret *
Calcium Oxide	1305-78-8	1 - 5 Trade Secret *
Titanium Dioxide	13463-67-7	< 3 Trade Secret *
Ethylbenzene	100-41-4	< 2 Trade Secret *
Petroleum Distillate	64742-47-8	< 2 Trade Secret *
Carbon Black	1333-86-4	< 0.3 Trade Secret *
P,P'-methylenebis(phenyl isocyanate)	101-68-8	< 0.2 Trade Secret *
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	0.01 - 0.1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Protect from sunlight. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	

Ethylbenzene	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
P,P'-methylenebis(phenyl isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m3(0.02 ppm)	
FREE ISOCYANATES	101-68-8	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
P,P'-methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
Calcium Oxide	1305-78-8	OSHA	TWA:5 mg/m3	
Calcium Oxide	1305-78-8	ACGIH	TWA:2 mg/m3	
Xylene	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
Xylene	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Carbon Black	1333-86-4	CMRG	TWA:0.5 mg/m3	
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	CMRG	TWA(as respirable dust):5 mg/m3	
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	CMRG	TWA:1 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., Skin Notation
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., Skin Notation
Petroleum Distillate	64742-47-8	CMRG	TWA:165 ppm	
Poly(Vinyl Chloride) Polymer	9002-86-2	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Mild xylene odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Boiling Point	>=137 °C
Flash Point	No flash point
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Density	1.2 g/ml
Specific Gravity	1.2 [<i>Ref Std: WATER=1</i>]
Solubility in Water	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	>=200 °C
Decomposition temperature	<i>No Data Available</i>
Viscosity	>=300,000 centipoise [<i>@ 73.4 °F</i>]
Hazardous Air Pollutants	7.3 % weight [<i>Test Method: Calculated</i>]
VOC Less H2O & Exempt Solvents	55 g/l [<i>Test Method: tested per EPA method 24</i>]
Solids Content	91 - 95.4 % weight

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines
Alcohols
Water

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Urethane Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Vinyl Chloride) Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Vinyl Chloride) Polymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Calcium Oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Petroleum Distillate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Petroleum Distillate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Petroleum Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
P,P'-methylenebis(phenyl isocyanate)	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
P,P'-methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.369 mg/l
P,P'-methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Rat	LD50 3,125 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Poly(Vinyl Chloride) Polymer	Professional judgement	No significant irritation
Xylene	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Calcium Oxide	Human	Corrosive
Ethylbenzene	Rabbit	Mild irritant
Petroleum Distillate	Rabbit	Mild irritant
Carbon Black	Rabbit	No significant irritation
P,P'-methylenebis(phenyl isocyanate)	official classification	Irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Calcium Oxide	Rabbit	Corrosive
Ethylbenzene	Rabbit	Moderate irritant
Petroleum Distillate	Rabbit	Mild irritant
Carbon Black	Rabbit	No significant irritation
P,P'-methylenebis(phenyl isocyanate)	official classification	Severe irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Titanium Dioxide	Human and animal	Not sensitizing
Ethylbenzene	Human	Not sensitizing
Petroleum Distillate	Guinea pig	Not sensitizing
P,P'-methylenebis(phenyl isocyanate)	official classification	Sensitizing
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Guinea pig	Sensitizing

Respiratory Sensitization

Name	Species	Value
P,P'-methylenebis(phenyl isocyanate)	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
Poly(Vinyl Chloride) Polymer	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Calcium Oxide	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	In Vitro	Not mutagenic

Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
P,P'-methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Poly(Vinyl Chloride) Polymer	Not Specified	Rat	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Petroleum Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
P,P'-methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Poly(Vinyl Chloride) Polymer	Not Specified	Not toxic to development	Mouse	NOAEL Not available	during gestation
Xylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
P,P'-methylenebis(phenyl isocyanate)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Does not cause effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

						Duration
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg	not applicable
Calcium Oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Petroleum Distillate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
P,P'-methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Poly(Vinyl Chloride) Polymer	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.013 mg/l	22 months
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system hematopoietic system muscles kidney and/or bladder respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the	Rat	NOAEL 900	2 weeks

			data are not sufficient for classification		mg/kg/day	
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	All data are negative	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months
Carbon Black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
P,P'-methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

Name	Value
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard
Petroleum Distillate	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Xylene	1330-20-7	Trade Secret < 6
Xylene (Benzene, 1,2-dimethyl-)	1330-20-7	< 6
Xylene (Benzene, 1,3-dimethyl-)	1330-20-7	< 6
Xylene (Benzene, 1,4-dimethyl-)	1330-20-7	< 6
Xylene (Benzene, dimethyl-)	1330-20-7	< 6
Ethylbenzene	100-41-4	Trade Secret < 2

15.2. State Regulations

Contact manufacturer for more information

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
BUTYL BENZYL PHTHALATE	85-68-7	Developmental Toxin
Ethylbenzene	100-41-4	Carcinogen
Carbon Black	1333-86-4	Carcinogen
Titanium Dioxide	13463-67-7	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	25-8775-6	Version Number:	5.00
Issue Date:	09/30/15	Supersedes Date:	05/11/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com